





中国认可 国际互认 检测 TESTING CNAS L4743

**Test Report** 

Report No.: AJFS2306004999FF

OFF Date: JUL.20, 2023

Page 1 of 8

Sample Name:CASTELLATED PANELSGS Ref No.:NJIN2306000770PL02Spec.:219H26Material and Mark:WOOD PLASTIC COMPOSITE

## Manufacturer: NANJING JUFENG ADVANCED MATERIALS CO., LTD.

The above sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion arising therefrom. Results apply to the sample as received.

\*\*\*\*\*

## Test Requested:

- 1. AS/NZS 1530.3:1999 Methods for fire tests on building materials, components and structures Part 3: Simultaneous determination of ignitability, flame propagation, heat release and smoke release.
- 2. AS ISO 9239.1-2003(R2016) Reaction to fire tests for floorings —Part 1: Determination of the burning behaviour using a radiant heat source.

Test Results: -- See attached sheet --

## Test Period:

Sample Receiving Date	:	JUN.13, 2023
Test Performing Date	:	JUN.13, 2023 TO JUN.27, 2023

Signed for and on behalf of SGS-CSTC Standards Technical Services Co., Ltd. Anji Branch

Echo Li Approved Signatory





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.gsc.com/enTerms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.gsc.com/enTerms-and-Conditions.aspx and, for electronic format documents, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document. This document cannot be reproduced accept in full, without prior written approval of the Company. Any unauthorized alteration, forger or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone;(86-755) 8307



Report No.: AJFS2306004999FF Date: JUL.20, 2023

# 1. AS/NZS 1530.3:1999

**Test Report** 

## I. Test conducted

This test was performed in accordance with AS/NZS 1530.3:1999 Methods for fire tests on building materials, components and structures Part 3: Simultaneous determination of ignitability, flame propagation, heat release and smoke release.

## II. Sample details

Description	Castellated Panel
Color	Brown
Thickness	26.5 mm
Density	13.7 kg/m <sup>2</sup>
Specimen size	600mm×450mm
Test surface	Marking surface

	Temperature ( $^{\circ}$ C)	Humidity (%)	Duration (d)
Conditioning	<b>20±2</b> ℃	65±5%	7

Note: The specimens shall be conditioned to constant mass (see ISO 291).

## Mounting or fixing method for test sample:

Using fibre-reinforced cement board as substrate, hold the sample and substrate against the specimen support frame by using the specimen clamping ring. No joint in the specimens.

## III. Test results

## The mean values and standard errors:

Items		Mean value	Standard error	
Ignition Time, (min)		NI	NA	
Flame propagation time, (s)		NA	NA	
Heat release integral, (Kj/m	Heat release integral, (Kj/m <sup>2</sup> )		NA	
Maximum optical density,	Ignition specimen			
D (m <sup>-1</sup> ) Non-ignition specime		0.9611	0.0042	
Ignition specimen				
Smoke release, lg D	Non-ignition specimen	-0.0172	0.0019	

Note: NI-Not ignition; NA-Not applicable



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions,sapx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Commat.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document aspx. Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or results shown in this test report refer only to the sample(s) tested and such sample(s) are related for 30 days only. Attention: To chock the suthenticity of testing / Inspection report & certificate, please contact us at telephone: (86-755) 8307



# Test Report Report No.: AJFS2306004999FF Date: JUL.20, 2023 Page 3 of 8

## Note:

1) Where all specimens do not ignite, means and standard errors for smoke release shall be reported separately for those specimens that ignite and those that do not ignite. The higher of the two values shall be reported as the smoke released for the material or component.

2) Where all specimens do not ignite, indices for smoke developed shall be reported separately for those specimens that ignite and those specimens that do not ignite. The higher of the two values shall be reported as the smoke developed index for the product.

## **Regulatory Indices:**

Items	Regulatory Indices
Ignitability index (Range 0 to 20)	0
Spread of flame index (Range 0 to10)	0
Heat evolved index (Range 0 to 10)	0
Smoke developed index (Range 0 to 10)	7

## **Supplementary Observations:**

- (a) Number of specimens tested: 6
- (b) The number of specimens that ignite: No
- (c) Where flashing was encountered, and ignition was based on a 10-second flash: No
- (d) The number of specimens did emit a radiation intensity rise of 1.4Kw/m<sup>2</sup>: No
- (e) Any observations of associated phenomena: No
- (f) Others: No



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/an/Terms-and-Conditions.aspx.and, for electronic Documents, subject to Torms and Conditions for Electronic Documents and the Dic/www.sgs.com/an/Terms-and-Conditions/Terms-eDocument.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document caes not experient and the provide the terms action document. This document is and without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is analytical the sample(s) tested and such sample(s) are retained for 30 days only. Attention's chaet the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307



# Test Report Report No.: AJFS2306004999FF

Date: JUL.20, 2023

Page 4 of 8

Table 1 Indices for spread of flame

1.33 x mean flame propagation time, s		Index
≥270		0
≥240	<270	1
≥210	<240	2
≥180	<210	3
≥150	<180	4
≥120	<150	5
≥90	<120	6
≥60	<90	7
≥30	<60	8
≥10	<30	9
	<10	10

#### Table 2 Indices for heat evolved

Mean value of the integral from the radiation intensity curves Kj/m <sup>2</sup>		Index
	<25	0
≥25	<50	1
≥50	<75	2
≥75	<100	3
≥100	<125	4
≥125	<150	5
≥150	<175	6
≥175	<200	7
≥200	<225	8
≥225	<250	9
≥250		10



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document can be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unawful and offenders may be prosecuted to the fullest extent of the authenticity of the sample(s) tested and such sample(s) are retained for 30 days only. Attention: O check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307



## Test Report Report No.: AJFS2306004999FF

Table 3 Indices for smoke developed

	Mean optical density, m <sup>-1</sup>			Indox	
Expressed in	terms of K*	Expressed	numerically	Index	
	<k< th=""><th></th><th>&lt;0.0082</th><th>0†</th></k<>		<0.0082	0†	
≥K	<2K	≥0.0082	< 0.0164	1	
≥2K	<2²K	≥0.0164	< 0.0328	2	
≥2²K	<2 <sup>3</sup> K	≥0.0328	< 0.0656	3	
≥2³K	<24K	≥0.0656	<0.131	4	
≥2 <sup>4</sup> K	<25K	≥0.131	< 0.262	5	
≥2⁵K	<2 <sup>6</sup> K	≥0.262	< 0.525	6	
≥2 <sup>6</sup> K	<2 <sup>7</sup> K	≥0.525	<1.05	7	
≥2 <sup>7</sup> K	<28K	≥1.05	<2.10	8	
≥2 <sup>8</sup> K	<2 <sup>9</sup> K	≥2.10	<4.20	9	
≥2 <sup>9</sup> K		≥4.20		10	

\* Where K is a constant = 0.0082

<sup>†</sup> Where doubt exists in the resolving of optical density below 0.016 m<sup>-1</sup> the index allotted should be '0 to 1'.

## Statement:

- 1) The results only apply to the specimen mounted as described in this report.
- 2) The results of this fire test may be used to directly assess fire hazard, but it should be recognized that a single test method will not provide a full assessment of fire hazard under all fire conditions.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.gas.com/en/Terms-and-Conditions.aspx and, for electronic Documents at http://www.gas.com/en/Terms-and-Conditions.aspx and, for electronic Documents at http://www.gas.com/en/Terms-and-Conditions.aspx and, for electronic Document as thttp://www.gas.com/en/Terms-and-Conditions.aspx and, for electronic Document as the titre of the second conditions for the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document is unlawful and offenders may be prosecuted to the fullest extent of the automatics at the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307



Report No.: AJFS2306004999FF

2306004999FF Date: JUL.20, 2023 Page 6 of 8

# 2. AS ISO 9239.1-2003

**Test Report** 

## I. Test conducted

This test was conducted as per AS ISO 9239.1-2003(R2016) Reaction to fire tests for floorings —Part 1: Determination of the burning behaviour using a radiant heat source.

## II. Sample details

Sample description	Castellated Panel
Color	Brown
Thickness	26.5mm
Density	13.7 kg/m <sup>2</sup>
Test surface	Marking surface
Specimen size	1050mm×230mm

## Conditioning:

Prior to testing, the sample was conditioned to constant mass at temperatures of 23±2°C and at a relative humidity of 50±5% for at least 48 h, until constant mass is achieved.

## Mounting of Test Assembly:

Fibre cement board, with its density approximate 1800kg/m<sup>3</sup>, thickness approximate 9mm, is as the substrate. The test specimens are fixed mechanically to the substrate. No joint in the specimens.

## III. Test results

Distance (mm)	S1	S2	S3	
Distance (mm)	Time (min:s)	Time (min:s)	Time (min:s)	
50	05:06	05:12	05:23	
100	05:19	05:40	06:18	
150	06:12	06:08	07:16	
200	07:06	06:16	07:38	
250	07:48	07:41	08:29	
300	10:05	10:16	11:49	
350	11:13	11:08	12:36	
400	11:41	12:06	13:07	
450	13:38	14:16	15:28	
500	15:18	16:22	17:49	
550	21:38	22;18	20:16	
600	22:36	23:46	23:33	
650	25:16	26:18	26:06	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions or Electronic Documents after the third of the theorem and the terretain and t



**Test Report** 

Report No.: AJFS2306004999FF

6004999FF Date: JUL.20, 2023

0, 2023 Page 7 of 8

700			
750			
800			
850			
900			
950			
1000			
Extinguishing time (min:s)	30:00	30:00	30:00
The final maximum flame spread distance (mm)	680	650	660

	S1	S2	S3	Average
Flame front distance at 10 min (mm)	290	290	280	287
Flame front distance at 20 min (mm)	530	530	520	527
Flame front distance at 30 min (mm)	680	650	660	663
Heat Flux at 10 minutes, HF-10 (kW/m <sup>2</sup> )	7.6	7.6	7.8	7.7
Heat Flux at 20 minutes, HF-20 (kW/m <sup>2</sup> )	3.2	3.2	3.4	3.3
Heat Flux at 30 minutes, HF-30 (kW/m <sup>2</sup> )	2.0	2.0	2.2	2.1
The integral of the smoke (% $ imes$ min)	19.8	20.3	21.6	20.6
Max. light attenuation (%)	128.8	130.6	126.7	128.7

## Summary of results:

	S1	S2	S3	Average
CHF	2.0	2.0	2.2	2.1

## Statement:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate partles to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are relatined for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-75) 8307



# **Test Report**

Report No.: AJFS2306004999FF

Date: JUL.20, 2023

Page 8 of 8

**Photo Appendix:** 



SGS authenticate the photo on original report only

\*\*\*End of Report\*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions or Electronic Documents after the third of the theorem and conditions are the electronic Document as the three of the information contained herein reference of the document as divised that information contained herein reference reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document is individued of the content is understruction at the time to the fullest extent of the accument is understruic and the company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is understruic and the sample(s) tested and such sample(s) tested and such sample(s) are takened for 30 days only. Attention: Or check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 e:(86-755) 8307 ng